

7950 Alphanumeric Pager

Getting Critical Messages to the Right People – When Every Second Counts

- Easy-to-use pager
- Two or four line alphanumeric display (with bold font feature)
- Up to 80 days of battery life
- Specially designed durable plastic enclosure
- Programmable by hand or USB software
- Up to eight cap codes
- Priority override – override silent/vibrate mode for code calls or critical alarms



Robust Alphanumeric Pager

The 7950 alphanumeric pagers from Commtech Wireless, a division of Amcom Software, include a number of versatile and indispensable features—all wrapped in a robust, durable casing. The plastic enclosure for the 7950 pagers has been rigorously tested to handle the toughest environments. These pagers boast a plastic casing which is triple the thickness of other market offerings, a wrap-around holster to protect the LCD, and a superior mechanical design to protect against the impact of drops. Colour-coded medical-grade rubber housing is also available to cushion impact further and protect against liquid entering the device (ingression).

Ease of Programming & Compatibility

Each 7950 can be configured to display only the options you want each user to access. This keeps users from accidentally reprogramming their pagers and turning off key settings. It also minimises the number of support calls needed. Many features within the 7950 can be programmed by hand or advanced programming can be managed via a USB programming cable connected to your PC. The 7950 series is compatible with all leading paging systems, as well as most wide-area paging carriers.

Priority Override for Code Calls and Emergencies

During transmission of a high-priority message, a pager on an inaudible setting can be forced to sound an audible tone with the priority override feature. This is critical for events such as code calls and other emergency situations.

Vibrate or Tone Differently for Different Calls

Code calls will beep or vibrate in a special alert pattern, while normal messages will vibrate in a standard fashion. This allows the user to know immediately how urgent the message is without even having to look at the pager.

Rechargeable Option

Any standard 7950 can be configured to operate as a rechargeable pager through a simple software modification and with the addition of a rechargeable battery. Chargers are available as an additional accessory.

Technical Specifications

7950 Alphanumeric Pagers	
Model No.	7950 VHF 7950 UHF
Frequency	VHF: 138-143MHz, 143-151MHz, 151-159MHz, 159-167MHz, 167-174MHz UHF: 448-452MHz, 452-456MHz, 456-460Hz, 460-464MHz, 464-468MHz
Signal Transmission Type	POCSAG
Cap Codes	8, Frame Independent
Message Capacity	50 Messages 512 Characters per Message
LCD Display	2 Lines, 20 Characters Per Line 2 Lines (Bold), 15 Characters Per Line 4 Lines, 20 Characters Per Line
Backlit LCD	White LED
Channel Spacing	25KHz WB or 12.5KHz NB (on request)
Frequency Deviation	±4.5KHz WB or ±2.5KHz NB (on request)
Data Transmission Rate	512/1200bps or 2400bps
Receiving Sensitivity	512bps 5uV/m, 1200 bps 7uV/m, 2400bps 9uV/m
Temperature / Humidity	-10°C (14°F) to +50°C (+122°F) @ 95% humidity
Dimensions (without holster)	70 (L) x 49 (W) x 19 (H)mm 2.7 (L) x 1.9 (W) x 0.7 (H) inches
Weight	135g (4.6 oz) including battery
Battery Life	Up to 80 days using AA Alkaline Battery
Approvals	CE / FCC / ACA C-tick / RoHS / IC

Two-line Display



Bold Display



Four-line Display



To learn more about Commtech Wireless products and solutions, please visit www.amcomsoftware.com.au